



# ARM-R-LITE

800-554-5816

STEEL AND ALUMINUM COMBINATION DOORS

UA/USES, APPLICATIONS

## NEW ARM-R-THERM H-16 INSULATOR



Newton Fire Department—Newton, NJ

**\*ANY SIZE UP TO 28'6" WIDE IN STOCK. FULL VIEWS UP TO 24'2" WIDE.**

### INTRODUCTION

The new, improved **H-16 INSULATOR** model was developed to meet the needs of today's heated buildings. This rugged, heavy-duty product has an R-value of 14.5. 40 years of technology backs our Insulator. High-speed production ensures fast delivery times for new projects or replacements parts.



**PEDESTRIAN PASS DOOR AVAILABLE!**

OP/OVERALL PRODUCT, IN PLACE

**CLASS 1 FIRE RATED!**

### CROSS SECTION



### SPECIFICATIONS

Arm-R-Lite Door Manufacturing Company's new Arm-R-Therm **H-16 INSULATOR** model insulated steel sectional upward acting doors embody the following particulars:

#### SECTIONS

- Foamed-in-place construction—CFC-free.
- 1 1/2" thickness.
- Exterior and interior skins .019 thickness (standard 26 gauge)—*best lead times*. Hot-dipped G-90 galvanized steel.
- **20 gauge skins available.**
- Siliconized polyester white, stucco embossed, wood grain finish.
- Built-in reinforcing plates for hardware attachment.
- R-value—**14.5**.
- End caps—galvanized steel.
- Shadow lines add strength and attractive pattern.
- **Class 1 Fire Rated!**

**ROLLERS:** Heavy-duty ball bearings with hardened inner race.

**WINDOW LITES:** 24" x 12", 24" x 8" or full vision aluminum sections up to 24'2" wide available: extruded aluminum sections of welded construction provide 1/2", 3/4" or 1 1/4" insulated glass.

**TRACK:** Arm-R-Lite galvanized 2" or 3" track.

**HARDWARE:** Galvanized stamped steel, 14 gauge.

UA/USES, APPLICATIONS

## NEW THERMAX MODEL

**3" foamed-in-place with an R value of 25**

### FOR EXTREMELY HARSH ENVIRONMENTS

If you need specially insulated doors for areas subjected to extreme hot or cold temperatures or for refrigerated areas, use the 3" foamed-in-place Arm-R-Lite **THERMAX** model. With an R-value of **25**, its polyurethane insulation will stand up to any temperature test. For more details, consult our factory.