

Industrial-Duty Hoist Operator

COMMERCIAL DOOR OPERATORS

MODEL

H



Logic 3.0 Technology
Elite Series™ Commercial Door Operators are engineered, manufactured and tested to provide reliable service to meet the toughest commercial applications.

Added Value

- Built-in 3-channel, 3.0MHz radio receiver accepts up to 23 Security+® or universal DIP switch remote controls.
- All LiftMaster® 3-button remotes can be programmed for open/close/stop operation.
- Maintenance Alert System™ lets you establish a routine maintenance schedule based on the number of cycles and/or operator time. Includes self-diagnostic system for easy troubleshooting.
- Timer-to-close may be set to close in 3-second or 1-minute increments.
- Thermal motor overload can be reset from the 3-button control station.
- Built-in programmable end-stop.
- Built-in programmable maximum run time.

Reliability

- Selfless motor eliminates stuck start switch and motor malfunctions of single phase operators.
- All high-voltage connections have been removed from the board for safer installation and improved reliability.
- 1-1/2 second delay-on-reverse helps prevent door and operator wear.

Programming Simplicity

- Selector dial replaces DIP switches for selecting wiring types and programming, including fullcut and non-fullcut wiring.
- Diagnostic LEDs speed installation and troubleshooting.
- Motor direction jumper lets you change motor direction by simply moving a jumper.

- Continuous-duty high-starting torque motor
- Universal-mount frame design
- Industrial ball bearings on output shaft
- Emergency chain hold with electric interface
- UL® 208300, 460v, 575v, 24v NEC Class 2 Circuit with 400k transformer



Includes the Logic 3.0 board and the exclusive Maintenance Alert System™

CHAMBERLAIN®

LiftMaster
ELITE SERIES™ LOGIC 3.0