



Solid steel construction is the basis for the Model 1000.

Two tough steel skins surround 2 inches of CFC-free polystyrene insulation. In addition, a thermal break creates a barrier to keep heat and cold from transferring through the door. Each Model 1000 features heavy-duty hardware for smooth operation.

To help resist dents, the outer steel skin is made of strong

24-gauge steel and the interior skin is made of 27-gauge steel.

The interior and exterior faces of the door feature stucco

embossing and the exterior has shallow ribs. The Model 1000 is

available prepainted in Commercial White.

Construction

Model 1000

Heavy-duty 2" Insulated Steel Door





TRIPLE-LAYER

Steel + Insulation + Steel

Track: All Amarr Doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit our website at www.amarr.com.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

PANEL



RIBBED PANEL WITH STUCCO EMBOSSMENT

WINDOW OPTIONS





24" X 12" SSB OR INSULATED GLASS

24" X 4" PLEXIGLAS

COLORS

Actual paint colors may vary from samples shown.



Amarr steel doors arrive pre-painted; for custom colors, exterior latex paint must be used. Visit *amarr.com* for instructions on painting.

WARRANTIES

- 10-year Limited Warranty on the paint and finish
- 1-year Limited Warranty on hardware
- See your dealer or visit amarr.com for complete warranty details

165 Carriage Court Winston-Salem, NC 27105 800.503.DOOR www.amarr.com

FOR PRODUCT BINDER: 1.800.503.3667

FOR TECHNICAL QUESTIONS: 1.877.512.6277