



Amarr's Model 1380 features two steel skins surrounding

1 3/8" inches of CFC-free polystyrene. Each skin is made of 27-gauge steel to provide a solid wall of protection from the elements. Our 4-step insulation system features insulation, weather-stripping, thermal break, and tongue and groove construction for a snug fit between sections.

The exterior face is stucco embossed and ribbed with shallow grooves. The interior surface is stucco embossed. Model 1380 is available prepainted in Commercial White.

Construction

Model 1380

Medium-duty 1 3/8" Insulated Steel Door





TRIPLE-LAYER

Steel + Insulation + Steel

Track: All Amarr Doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow the Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit our website at www.amarr.com.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

PANEL



RIBBED PANEL WITH STUCCO EMBOSSMENT

WINDOW OPTIONS





24" X 12" SSB OR INSULATED GLASS

24" X 4" PLEXIGLAS

COLORS

Actual paint colors may vary from samples shown.



Amarr steel doors arrive pre-painted; for custom colors, exterior latex paint must be used. Visit *amarr.com* for instructions on painting.

WARRANTIES

- 10-year Limited Warranty on the paint and finish
- 1-year Limited Warranty on hardware
- See your dealer or visit amarr.com for complete warranty details



165 Carriage Court Winston-Salem, NC 27105 800.503.DOOR www.amarr.com

FOR PRODUCT BINDER: 1.800.503.3667

FOR TECHNICAL QUESTIONS: 1.877.512.6277