



The Model 2700 is Amarr's top-of-the-line high R-Value door designed exclusively for the Commercial and Industrial sectional overhead door market. It is constructed using foamed-in-place polyurethane insulation which creates a strong monolithic panel that is energy efficient.

Each Model 2700 is secured with standard 14-gauge, galvanized steel hinges. The interior skin of each section has two continuous horizontal 20-gauge reinforcing strips. The section joint is thermally broken and chemically bonded with a pressure-sensitive adhesive sealant. An EPDM rubber weather seal further enhances the performance of the joint.

COLORS

Actual paint colors may vary from samples shown.



COMMERCIAL WHITE



BROWN

Amarr steel doors arrive pre-painted; for custom colors, exterior latex paint must be used. Visit *amarr.com* for instructions on painting

WARRANTIES

- 10-year Limited Warranty on the paint and finish
- 1-year Limited Warranty on hardware
- See your dealer or visit amarr.com for complete warranty details

Construction

Model 2700

Heavy-duty 2" Foamed-in-Place Door





TRIPLE-LAYER

Steel + Insulation + Steel

Track: All Amarr Doors are available with both 2" or 3" track in Standard Lift, High Lift, Vertical Lift, Low Headroom, and Follow-the-Roof Pitch. Custom track configurations are also available. For drawings and more information, please visit our website at www.amarr.com.

Hardware: Amarr hardware includes minimum 14-gauge galvanized steel hinges and 13-gauge galvanized steel track brackets. All rollers have minimum 10-ball bearings.

Springs: Torsion springs are oil tempered, helical wound and custom computed for each door for a minimum 10,000 cycle life. Optional springs are available up to 100,000 cycle life.

PANEL





RIBBED PANEL WITH STUCCO EMBOSSMENT

OPTIONAL FULL-VIEW PANEL

WINDOW OPTIONS







24" x 6" DOUBLE INSULATED ACRYLIC WINDOWS WITH BLACK FRAME WHITE FRAME AVAILABLE (SPECIAL ORDER)



24" X 12" INSULATED GLASS



165 Carriage Court Winston-Salem, NC 27105 800.503.DOOR www.amarr.com

FOR PRODUCT BINDER: 1.800.503.3667

1.877.512.6277

FOR TECHNICAL QUESTIONS: