

Model 9600

More Insulation Plus Design Options



www.wayne-dalton.com



Door Construction

- Embossed, high tensile steel front panels give the look of wood with the strength of steel.
- Two-coat, baked-on polyester finish is virtually maintenancefree. This finish also makes an excellent base if you repaint to match the existing exterior colors of your home.
- The foamed-in-place polyurethane insulation is chemically bonded to each steel section, creating a structure with higher strength and dent resistance.
- Heavy-gauge steel wraparound end caps trim-out door edges for better appearance, improved strength and protect the foamed-in-place polyurethane insulation from damage.
- Integral foam-filled horizontal struts at the top and bottom of door sections add rigidity for long life and smooth operation – extra strength without extra weight.
- The polyurethane foam is CFC-11-free, so it's environmentally friendly.

- Sound-absorbing insulation makes the door operate quieter and eliminates wind-rattling.
- Attractive, low-profile hinges provide maximum strength between sections and add stability compared with ordinary vertical hinges. Hinges are factory-installed for proper alignment and smoother door operation.
- Bulb-shaped bottom seal remains flexible even in extreme cold to help keep the bad weather outside.
- SilentGlide[™] rollers with nylon tires and solid steel shafts provide years of smooth, quiet, dependable service.
- Protective polymer caps add a finishing touch to the reinforcing struts.

Model 9600 Specifications (Continued)

Design

- Steel front panels are embossed with a wood-grained texture giving the look of genuine wood.
- All panel designs available in white, taupe, almond and brown.

Ranch





	ТП			Π
		TTT	ITT	
		Ш	Ш	
THE	П	TTT	TT	П

Safety & Security

- Pinch-resistant design helps push fingers out of harms way if accidentally placed near a closing door.
- TorqueMaster[®] counterbalance completes an integrated door system that's much cleaner and safer than other counterbalance spring systems. It mounts directly above the door and has no exposed springs, horizontal cables or pulleys.
- Tamper-resistant safety bottom brackets help avoid possible injury by preventing inadvertent loosening when the counterbalance cables are still under tension.

Warranty

Model 9600 offers a Lifetime Limited Warranty against cracking, splitting, rusting through or section deterioration. See dealer for complete warranty details.



Even More Features

Why not buy a new *i*drive[®] wall-mounted opener or *pro*drive[™] ceiling-mounted opener to go with your new door? Only Wayne-Dalton manufactures and designs both the door and opener to work together as one complete system.

©2007 Wayne-Dalton Corp. www.wayne-dalton.com Item # 328666 1/07

Windows

• Many decorative window inserts are available to enhance the look of your garage door, which in turn enhances the look of your home. Here are just two examples. See brochure or web site for all options.

on I Cathedral I

Colors



SEE ALL THE LOOKS AVAILABLE ON OUR DOOR SELECTION CENTER AT www.wayne-dalton.com

Energy Efficiency & Noise Control

- The core delivers R-10 insulation, more than twice as much as the same thickness of common polystyrene insulation.
- Bulb-shaped bottom seal remains flexible even in the cold to keep out bad weather.
- The foamed-in-place insulation helps block street noise from entering into living areas that adjoin the garage.



D	eale	er In	npri	int .	Area