

## Medium-Duty Logic Hoist Operator

COMMERCIAL INDUSTRIAL GATEWAY

**MH**

MODEL



- Adjustable travel switch
- Standard travel limit
- High-strength torsion hoist with overload protection
- Compact design
- Emergency chain hoist with locking controls



Includes the Medium-Duty Logic Board with built-in Receiver



Featuring built-in radio receiver compatible with up to 20 Security+™ or universal DIP switch remote controls  
Requires receiver and transmitter.

### Medium-Duty Logic Technology

Offers an innovative design that provides reliable service and exceptional value to economically meet the toughest commercial applications.

#### Added Value

- Medium-Duty Logic programmable integrated circuit board
- Integrated 3-channel relay
  - User-program up to 20 Chamberlain® 315 MHz remote controls
  - Accepts Security+™ and DIP switch remote controls
- Compatible with 3-button remote controls for quick troubleshooting operation
- Programmable (L1 or R1) sensing sensors
- Integrated timer-to-close (TTC)
  - Programmable from 2 to 60 seconds (DIP L1 or T1/T2-L1/L2 photo-sensor must be selected)
- Integrated RFI receptor (maximum rssi value)
- Enhanced抗干扰性 against transient overvoltage conditions
- 3-button control station included

#### Also available, Mechanical dual-relay version (M)

110V - 240VAC, NEC, Class 2 Circuit with 20VA transformer

Decades-old, dual-relay operator control system. Control system requires easy selection between R1 and L1 wiring by moving a single wire.

CHAMBERLAIN®

**LiftMaster**  
MEDIUM DUTY LOGIC